

Technical Data Sheet



COVERMATT

A water-borne high opacity first decoration matt emulsion for interior use only. Recommended for use over new work. Specially formulated to allow surfaces to 'breathe' and dry naturally.

AVAILABILITY

Colour Range See Crown Trade Literature

Packaging 5 litre. 10 litre in White and selected colours

PROPERTIES

Drying Time Under normal drying conditions touch dry 1-2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.

Finish Matt

Composition Pigment: Titanium Dioxide, coloured pigments and extenders.
Binder: Vinyl acetate copolymer.
Solvent: Water.

Spreading Rate 11-16m² per litre dependant on smooth surfaces

Wet Film Thickness 90 micrometres at 11m² per litre.

Dry Film Thickness 22 micrometres at 11m² per litre.

Volume Solids 25% White other colours will vary.

Flash Point Not applicable.

VOC Content EU limit value for this product (cat.A/a): 75 g/l (2007) / 30 g/l (2010) This product contains max. 18 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Primer. Porous surfaces should be 'mist' coated with Crown Trade Covermatt thinned with up to 20% clean water.

COATING SYSTEM

Apply two coats as required.

APPLICATION

Stir well before use. Apply by brush or roller. For airless spray (dilution may be required). For further information contact the Crown Trade Customer Relations Team.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Trade products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information.
For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0845 389 9583

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

This information is correct at date of issue April 2008.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk