

## DESCRIPTION

Johnstone's Woodworks Sprayable Shed & Fence Treatment is the fastest way to colour and protect your garden timber with just one coat. The quick drying formulation is wax-enriched giving water repellence and superior protection from the sun's harmful UV rays. Specially developed for use with the Johnstone's Woodworks Shed & Fence Sprayer which allows you to spray and protect a single fence panel in less than 4 minutes\* with minimal effort.

\* Based on an average 6ft x 6ft fence panel.

## RECOMMENDED USES

INTERIOR

Exterior use for Shed and Fence panels.



## SPECIAL PROPERTIES

3 year colour retention. Resists harmful UV rays. Wax enriched and water repellent.

## COLOUR RANGE

Dark Oak, Dark Chestnut, Green, Rustic Red.

## FINISH

Matt.

## VOLUME SOLID

## COVERAGE

COVERAGE

6  
M<sup>2</sup>/LITRE

Johnstone's Woodworks Sprayable Shed & Fence Treatment will cover approximately 6 square metres per litre, depending on the nature and porosity of the surface. One coat is usually enough to cover your chosen timber.

## DRYING TIME

RECOAT

2  
HRS

Recoat after 2-4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position.

## THINNER

Water.

## VOC CONTENT

MINIMAL VOC content 0-0.29% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/e): 150g/l (2007) / 130g/l (2010). This product contains max 20g/l VOC.

## FILM THICKNESS

## SIZE

5 litre.

## PREPARATION

Ensure all timber is clean, dry and free from surface coatings, such as paint, varnish or polish. If the timber is affected by mould, lichen, algae or moss, use a fungicidal pre-treatment prior to application of the Shed & Fence Treatment.

Johnstone's Shed & Fence Treatment is not designed for use on planed timber or wood.

## APPLICATION



**SHAKE THOROUGHLY BEFORE OPENING.** Follow the instructions provided for assembly and use of the Johnstone's Woodworks Shed & Fence Sprayer. Whilst applying ensure gloves are worn to avoid staining hands. For best results hold the nozzle 30cm from the timber being treated. Spray one section at a time. Spray the edges and any vertical supports before spraying the centre area. Use a slow sweeping horizontal motion, turning at the end and overlapping approximately half of the previous pass each time. Re-pump the sprayer when the spray pattern weakens. It may take a couple of minutes before you perfect your technique. The final colour will depend on the original colour of the wood and the number of coats applied. Do not apply when the temperature is below 10°C, when rain is imminent, or in windy conditions. Avoid contact with plant life until dry. Wipe any splashes off leaves to avoid discolouration.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately with warm, soapy water and rinse thoroughly. Replace cap firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. To avoid the risk of spillage, always store and transport in a secure upright position.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Contains an algicide. It maybe harmful if swallowed.
- Do not breathe spray.
- In case of insufficient ventilation, wear suitable respiratory equipment.
- Keep out of reach of children.
- Safety data sheet available for professional user on request.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

