

DESCRIPTION

Johnstone's Universal Primer is a solvent-borne primer formulated for interior and exterior use on new or bare wood, metal, plaster and masonry. Based on an anti-corrosive zinc phosphate pigment and alkyd resin, it is particularly suitable for multi-surface work.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood, metal, plaster and masonry.

COLOUR RANGE

White and Red Oxide.

FINISH

Not applicable.

VOLUME SOLID

49%

COVERAGE



Approximately 11–13 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 3–4 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

High VOC content 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400g/l (2007).
This product contains max 400g/l VOC.

FILM THICKNESS

Wet: 83µm, dry: 41µm.

KEY PROPERTIES

- Contains a zinc phosphate, anti-corrosive pigment.
- Suitable for use on wood, metal and dry plaster.
- Especially suitable for multi-surface work.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel, remove all millscale and rust. Wear a suitable face mask when creating dust. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush or roller.
On woodwork apply by brush and work well into the grain. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Paint UN1263.
- Contains Tri Zinc Bis Orthophosphate.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Flammable
- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – Do not use solvent or thinners.
- Restrict interior use to small surfaces such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas - walls, floors or ceilings - or in confined spaces.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

SIZES

1 Litre, 2.5 Litre, 5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.